



Cleaning recommendation for brass and PVD surfaces

Suitable products:

- Neutral aqueous cleaning agents and neutral synthetic cleaning or wetting agents are suitable for removing loosely adhering dirt from coated surfaces

Important: The surfaces to be cleaned should be cleaned as mildly as possible and then rinsed thoroughly with water, as corrosion can be caused by residual salts, acids or alkalis. Never use abrasives or scouring agents!

Unsuitable products:

- Strongly acidic aqueous detergents: When using acetic acid, oxalic acid, phosphoric acid, the concentrations of more than 0.5 percent are not permissible. Other acids, such as hydrochloric acid, sulfuric acid, etc., in any concentration unsuitable
- Strongly alkaline, water-based cleaning agents: These products are generally prohibited for cleaning coatings
- Solvent cleaners Esters, ketones (such as acetone), glycol ethers, benzines, thinners (e.g., nitro thinner), stain remover, and chlorinated hydrocarbons are unsuitable
- Do not use products of unknown chemical origin
- During cleaning, the surfaces must be cold (temperature maximum = 30° C) and should not be directly exposed to the sun
- The cleaning agents must also be cold (temperature maximum = 30° C), please do not use spray steam products

This recommendation corresponds to the current general state of experience and does not lead to any legally binding effect. In case of doubt and in special cases, a preliminary test is required.

